G501975PEJ1880

USB3.0 PCI-Express Controller Card

Data Transfer Rate Reaches to 5.0Gb/s

User Manual
Ver. 1.00

All brand names and trademarks are properties of their respective owners

Features

1. Supports 4 downstream ports for all speeds
2. Single-lane (x1) PCI Express throughput rates up to 5 Gbps
3. Fully compliant with PCI Express base specification revision 2.0
4. Compliant with Universal Serial Bus 3.0 specification revision 1.0
5. Supports simultaneous operation of multiple USB 3.0, USB 2.0 and USB 1.1 devices.
6. Supports data rate: Super speed(5 Gb/s), high speed(480 Mb/s), full speed(12 Mb/s), low speed(1.5 Mb/s).
7. Compliant with Intel's extensible host controller interface specification revision 1.0

Hardware Installation

1. Turn off the power of your computer.
2. Unplug the power cord and remove your computer's cover.
3. Remove the slot bracket from an available PCI-E slot.
4. To install the board, carefully align the card's bus connector with the selected PCI-E slot on the motherboard. Push the board down firmly.
5. Attach your internal devices to the PCI-e EJ188 card.
6. Replace the slot bracket's fastening screw to secure the card.
7. Replace the computer cover and reconnect the power cord.

Driver Installation

1. Please insert the CD driver into your CD ROM.
2. Find the path into the CD ROM (X: \Etron \EJ188)
3. Double-click "setup".
4. Follow the on-screen instructions to complete the installation.
5. Restart windows to complete the installation.

System Requirements

Windows 7 / Vista / 2008 / 2003 / XP / 2000

Package Contents

- 1 x Driver CD
- 1 x User Manual
- 1 x USB3.0 PCI-Express Controller Card
- 1 x Low Profile Bracket (SY-PEX20135)